

HEADQUARTERS



-  Direzione
Progettazione
Lavorazioni meccaniche
Assemblaggio
-  Direction
Bureau d'etudes
Usinage, assemblage
Montage
-  Sales department
Design department
Machine shop
Final assembly
-  Direction
Oficina tecnica
Mecanizacion
Ensamblaje

Viale dell'Industria, 18 - 35014 - Fontaniva (PD) - Italy
Tel. +39 049 594 1924 - Fax +39 049 594 2115

PLANT II



-  Montaggio, carpenteria
e saldatura
-  Assemblage structure
et soudage
-  Frame assembly
and fabrication shop
-  Calderia y soldadura

Via Veneto, 21 - 35043 - Monselice (PD) - Italy



SAPRE COSTRUZIONI s.r.l.



info@pressix.it - www.pressix.it

info@saprecostruzioni.it - www.saprecostruzioni.it


PRESSIX®

STRAIGHT SIDE PRESSES

GAP FRAME PRESSES



CNV CNR4



CNR6



DM



DM CF
DM CC
DM LD
DM R2

Versions with:
One connecting rod (DM1).
Two connecting rods (DM2).
Fixed stroke length (CF).
Automatic adjustable stroke length (CC).
Link drive (LD).
Double back-gear (R2).

TECHNICAL DATA

Forza • Force
Puissance • Fuerza

Colpi nominali • Nominal speed
Vitesse nominale • Golpes nominal

Colpi con velocità fissa • Fixed speed
Coups/minute sans variateur • Golpes fijos

Colpi con velocità variabile • Variable speed
Coups/minute avec variateur • Golpes regulables

Corsa • Stroke length
Course • Carrera

Regolazione mazza • Slide adjustment
Réglage du coulisseau • Regulación del carro

Distanza banco-mazza* • Press shuheight*
Distance table-coulisseau* • Distancia mesa-carro*

Dimensioni del piano • Bolster area
Dimensions table • Dimensiones de la mesa

Dimensioni della mazza • Slide area
Dimensions du coulisseau • Dimensiones del carro

	GAP FRAME PRESSES												STRAIGHT SIDE PRESSES							
	CNV2	CNV4	CNV4	CNR4	CNR4	CNR4	CNR4	CNR6	CNR6	CNR6	CNR6	CNR6	DM2cc	DM2cc	DM2cc	DM2cc	DM2cc	DM2cc	DM2cc	
	25	40	65	50	65	80	100	100	130	160	200	250	125	200	250	315	400	500	630	
kN	250	400	650	500	650	800	1000	1000	1300	1600	2000	2500	1250	2000	2500	3150	4000	5000	6300	
Spm	132	125	120	77	53	53	45	45	48	45	36	33	50	42	40	38	30	31	35	
Spm	150	140	140	90	73	65	65	65	60	55	45	41	•	•	•	•	•	•	•	
Spm	100-200	60-180	60-180	40-120	38-115	38-115	30-90	30-90	27-80	23-70	20-60	19-57	30-180	30-140	30-100	30-90	20-80	25-60	25-60	
mm	5-75	5-100	8-120	4-110	8-120	8-120	10-130	10-170	13-160	12-180	16-220	19-250	20-180	20-220	30-260	40-315	40-315	40-315	40-400	
mm	50	70	100	70	100	100	100	100	110	110	120	130	150	150	200	200	200	250	250	
mm	270	240	320	275	320	370	370	350	430	440	450	480	450	550	600	700	750	800	750	
mm	360 x465	480 x650	580 x820	530 x770	580 x820	620 x880	660 x950	660 x1050	765 x1200	750 x1250	800 x1300	860 x1400	1000 x1400	1100 x1800	1200 x2000	1300 x2200	1300 x3000	1400 x3000	1400 x3000	
mm	160 x220	300 x370	340 x470	300 x450	340 x470	400 x500	450 x540	500 x650	550 x800	600 x850	600 x900	700 x1000	1000 x1400	1100 x1800	1200 x2000	1300 x2200	1300 x3000	1400 x3000	1400 x3000	

* Misurata al punto morto inferiore con regolazione della mazza tutta alta * At Bottom Dead Center with slide adjustment all up (SDAU) * Mesurée au P.M. B. avec réglage du coulisseau tout en haut * Al punto muerto inferior con carro regulación arriba